

# LV Series

Visual level indicators



## Technical data

### Electrical Oil Level Indicators

#### Visual level indicators

Multi-control range visual level gauges. The visual level gauges allow the liquid level to be checked in a clear and precise way at any time. The principle used is that of communicating vessels: the liquid goes through the level gauge by means of hollow screws, showing the user the each point inside the tank.

The level gauges can be equipped with a tap that stops the flow from the tank to the gauge.

C/C distances of 5-19.7 inch are fully interchangeable with all major level gauges. 'U' protection screen is normally fitted in order to ensure visibility on the front part of the level gauge, but if necessary, it can be turned 90° to deliver visibility on the right or left.

Minimum level signal which can be 'Normally Open, Normally Closed, or Exchange' contacts upon request

#### Available features:

- Ease of Use: The visual gauges allow the liquid level to be checked clearly at any time
- Electrically Safe: No electrical contact with fluid.
- Variability in Size: Multiple sizes and distances meet the needs for all customers and applicaitons.

#### LV SERIES

- Side mounted that can be turned to 90° to obtain visibility if needed
- 'U' protection screen with graduated scale fitted for visibility from all angles
- Maximum Tightening Torque: 10Nm
- Maximum pressure: 35 Bar
- M10 or M12 Screws recessed in the body

## Designation & Ordering code

### COMPLETE VISUAL OIL LEVEL INDICATORS

Series	Configuration example :						
<b>LV</b>	LV	20	T	A	P	M10	S01
Size							
10   20   30							
Thermometer							
S Without thermometer							
T With thermometer							
Seals							
A NBR							
V FPM							
Cover material							
P Polyamide							
Connections							
M10 M10							
M12 M12							
U38 3/8" UNC							
U12 1/2" UNC							
Execution							
S01 Tag MP Filtri, with nuts							
S02 Tag MP Filtri, without nuts							

