# OIL & GAS



# **HYDRAULIC FILTRATION**



Designing an effective filtration system requires a precise evaluation of its specific features, including: sensitivity of the individual components, degree and type of contamination, circuit pressure,

flow rate, environmental conditions, fluid used and intervention cycles with a guarantee of a longer life of the machines than expected.

#### STAINLESS STEEL HIGH PRESSURE FILTERS

Stainless steel construction ensures peak protection when operating in corrosive environments or aggressive fluids.

High pressure stainless steel filters are used to protect individual valves or the entire hydraulic circuit from contamination.



#### FILTERS FOR POTENTIALLY EXPLOSIVE ATMOSPHERE

Standard ATEX Directive 2014/34/EU and UK Regulation S.I. 2016 No. 1107 (as amended). There are two different markings, defined by the type of sealing material that determine the maximum operating temperature.



#### THE ATEX CERTIFIED MP FILTRI PRODUCTS ARE THE FOLLOWING



Filter with NBR seal in configuration zerospark\*

CE CK EX



II 3G Ex h IIC T6 Gc X II 3D Ex h IIIC T85°C Dc X T<sub>amb</sub>: -15°C ÷ +80°C, T<sub>max fluid</sub> +80°C

Filter with EPDM / FPM / MFQ seal in configuration zerospark\*

CE RE



II 3G Ex h IIC T6... T4 Gc X II 3D Ex h IIIC T85°C...T115°C Dc X T<sub>amb</sub>: -15°C ÷ +110°C, T<sub>max fluid</sub> +110°C



#### FILTER ELEMENTS

**DIFFERENT OPTIONS OF FILTER ELEMENTS** WITH THE MYCLEAN AND ZEROSPARK® CONCEPTS

Wide range of filter elements in various filtration grades for all MP Filtri filters and as market interchanges.



zerospark+°

THE ANTI-STATIC FILTERS THE ZANTISTATIC CONCEPT FOR OUR FILTERS





Zerospark® is a specialised solution designed to solve the problem of electrostatic discharge inside hydraulic filters. Caused by the electrical charge build-up due to the passage of oil through the filters, this can result in damage to filter elements, oils and circuit components. It can even cause fire hazards in environments where flammable materials are present.

#### TANK ACCESSORIES

((A))) MPFITRI

The complete range of tank accessories for hydraulic circuits comprises breather filters, filler and breather filters, filler caps, visual and electrical level indicators, pressure gauges selectors, flanges for fixing the oil tubes on the tank cover and inspection doors. Filler and breather filters have a dual function at the tank inlet in the filtration of the incoming air and the pre-filtration of the fluid through the basket, in order to prevent the entry of foreign bodies during the filling or refilling operations.







**LVA 20** 







**TA 70** 

**SAW TAP 90** 

**BELL-HOUSING** 

Bell-Housings are used as

range of hydraulic pumps

available on the international

connecting elements between

IEC electric motors and a wide

LVK

**RLG/LEN** STRC

# POWER TRANSMISSION



#### **COUPLINGS**

Drive couplings provide the means by which power is transmitted from the electric motor to the hydraulic pump.



SGE series **AKG** series





II 2G Ex h IIC T6...T4 Gb

Installation zone: zone 1 / 21 Dust group: IIIC Gas group: IIC

II 2D Ex h IIIC T85°C...T135°C Db

Ambient temperature: -30C°+ +120°C

market.



#### **ACCESSORIES**

Our accessories line completes the range, adding value and features to the motor pump unit.

# CONTAMINATION CONTROL SOLUTIONS

MP Filtri designs and manufactures a complete range of contamination control solutions aimed at increasing the life and the productivity of the hydraulic circuits. The technology developed by our Contamination Monitoring Products division allows preventive and predictive maintenance, guaranteeing

maximum continuity of operation, a longer life cycle of the components and a relative reduction in costs. A complete solution that combines highly functional and energy-efficient systems with a wide range of after-sales services.

# CONTAMINATION MONITORING **PRODUCTS**



LPA3 Portable **Light Extinction** Particle Analyser

### IN-LINE CONTAMINATION **MONITORS**



**ICM 2.0** In-Line Contamination Monitor



**ICM K 2.0 AZ2** In-line Contamination Monitor suitable for



# **MOBILE FILTRATION** UNITS



**UFM 051** 50 l/min

**UFM 015** 

15 l/min

(3.96 gpm)



(13.20 gpm)



**UFM 181** 90 I/min / 180 I/min (23.77 gpm / 47.55 gpm)

# WORLDWIDE NETWORK

CANADA • CHINA • FRANCE • GERMANY • INDIA • SINGAPORE UNITED ARAB EMIRATES • UNITED KINGDOM • USA



PASSION TO PERFORM

